

SP SPORT 6060



APPLICATION

An asymmetrical tyre offering exceptional performance. Increased groove density and distribution provides for very low noise generation and comfort. Provides sophisticated, discerning drivers with enhanced overall vehicle performance.

Feature: Stiffer blocks in the outer shoulder

Benefit: Provides precise steering response and cornering stability

Feature: More flexible inner shoulders and increased grooving

Benefit: Provides more grip and ensures optimum road contact

Feature: Increased groove density and distribution

Benefit: Provides for very low noise generation and enhanced drive comfort

Feature: The latest silica compounding innovations

Benefit: Provides the sophisticated and discerning driver with reduced fuel consumption due to minimised rolling resistance

Feature: Jointless Band Construction (JLB)

Benefit: Ensures the tyre retains its optimum shape when cornering for maximum steering response.

Tyre Size	Load Index	Speed Index	Overall Diameter (mm)	Section Width (mm)	Maximum Load (kg)	Maximum Pressure (kPa)	Recommended Rim (J)
-----------	------------	-------------	-----------------------	--------------------	-------------------	------------------------	---------------------

195/65 R 15	91	V	629	199	615	300	6.0
195/55 R 15	85	V	591	195	515	300	6.0
205/55 R 16	91	W	628	212	615	300	6.5
225/55 R 16	95	W	647	230	690	300	7.0
225/45 R 17	94	W	633	226	670	350	7.5
235/45 R 17	97	W	639	236	730	350	8.0
205/40 R 17	84	W	591	210	500	350	7.5
225/40 R 18	88	W	633	232	560	350	8.0
235/40 R 18	91	W	639	232	615	350	8.5

Tel: + 27 (0) 31 242 1111 Fax: + 27 (0) 31 242 1366

E-mail: marketing@dunlop.co.za

Website: www.dunloptyres.co.za

